

BLACK SIGNAL GENERATOR, NTSC/SDI OR PAL/SDI - BSG-26A



FEATURES

- 6 Outputs - Without SDI option: 6 NTSC
With SDI option: 4 NTSC, 2 SDI 525/60 (for BSG-26AN)
- 6 Outputs - Without SDI option: 6 PAL
With SDI option: 4 PAL, 2 SDI (for BSG-26AP)
- NTSC format analog & 525/50 serial digital (BSG-26AN)
- PAL format analog & 625/50 serial digital (BSG-26AP)
- Stand-alone box
- High Quality, Low Cost

SPECIFICATIONS

OUTPUTS

Blackburst (BSG-26AN)

Without SDI option:

(6) NTSC per RS-170A & ANSI/SMPTE 170M

With SDI Option:

(4) NTSC per RS-170A & ANSI/SMPTE 170M

(2) SDI per SMPTE 259M (NTSC)

Blackburst (BSG-26AP)

Without SDI option:

(6) PAL per CCIR 624-4

With SDI Option:

(4) PAL per CCIR 624-4

(2) SDI per SMPTE 259M

SCH Phase	0° ±5°
SCH Phase Jitter	2° p-p
Set-Up & Superblack	Jumper selection; +7.5, 0 IRE
Frequency/Stability	27.000000 MHz TCXO, 1 ppm/yr
Connectors	BNC (6)
Max Pwr Consumption	6 Watts
Input Voltage Range	90 to 255 VAC
Line Frequency	50 to 60 Hz

Prices and Specifications are subject to change without notice.